



BELT TECHNICAL DATA SHEET

TUFFY — EP160 2 PLY BR

BELT CONSTRUCTION: Two ply polyester/nylon, N grade black rubber 3.0mm top cover X 1.5mm bottom cover.

Colour	Black
Belt Thickness	6.5mm
Top Cover Thickness	3.0mm
Bottom Cover Thickness	1.5mm
Belt Weight	8.5kg/m ²
Coefficient of friction (On steel)	0.40
Minimum pulley Diameter	200mm (at ambient temperature)
Minimum back flex Diameter	260mm (at ambient temperature)
Belt Rating	EP160
Temperature Range	-30 to + 60 Deg C
Food Rating	N/A
Carcass construction	Polyester/Nylon Flexible
Stock width	1500mm
Manufactured width	2000mm



Recommended Splice	Step Join
Recommended fastener	Riv-nail or bolt hinged

Belt Characteristics Suitable for a wide range of Industrial applications.
Trough conveyors
N grade covers for general purpose
Light abrasion resistance.

Typical Applications Quarrying
Top soil / compost conveying
Sand, pumice, stone & aggregate
Waste recycling plants
Elevator bucket conveyors
General heavy duty industrial conveying

HAMILTON
HASTINGS

PH 07 849 9445
PH 06 843 2186

FAX 07 849 9456
FAX 06 879 9895

EMAIL sales@thl.net.nz
EMAIL sales@thl.net.nz

SPECIALISTS IN CONVEYOR BELTING & TRANSMISSION PRODUCTS

www.transmissionhouse.co.nz